

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 February 2005 (24.02.2005)

PCT

(10) International Publication Number
WO 2005/017234 A1

(51) International Patent Classification⁷: **C25C 3/06**,
3/08, 7/00

(21) International Application Number:
PCT/IB2004/051437

(22) International Filing Date: 10 August 2004 (10.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PCT/IB03/03651 14 August 2003 (14.08.2003) IB

(71) Applicant (for all designated States except US):
MOLTECH INVENT S.A. [LU/LU]; 6, rue Adolphe
Fischer, L-1520 Luxembourg (LU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NGUYEN, Thinh**,

T. [CH/CH]; Route du Grand-Lancy 165b, CH-1213 Onex
(CH). **SCHNYDER, Frank** [CH/CH]; Ch. des Sorbiers 7,
CH-1803 Chardonne (CH). **DE NORA, Vittorio** [IT/BS];
Sandrigham House, Nassau (BS).


(74) Agent: **CRONIN, Brian**; c/o Moltech S.A., Quai du
Mont-Blanc 21, CH-1201 Geneva (CH).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: METAL ELECTROWINNING CELL WITH ELECTROLYTE PURIFIER



(57) Abstract: A cell for electrowinning a metal, in particular aluminium, from a compound thereof dissolved in an electrolyte (30) comprises an anode (40) and a cathode (10,11) that contact the electrolyte (30), the cathode (10,11) being during use at a cathodic potential for reducing thereon species of the metal to be produced from the dissolved compound. The electrolyte (30) further contains species of at least one element that is liable to contaminate the product metal (20) and that has a cathodic reduction potential which is less negative than the cathodic potential of the metal to be produced. The cell further comprises a collector (50) for removing species of such element (s) from the electrolyte (30). During use the collector (50) is at a potential that is: less negative than the cathodic potential of the produced metal (20) to inhibit reduction thereon of species of the metal to be produced; and at or more negative than the reduction potential of the species of said element(s) to allow reduction thereof on the collector (50). The cell is so arranged that species of said element(s) are reduced on the collector (50) rather than on the cathode (10,11) so as to inhibit contamination of the product metal (20) by said element(s).



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only